

DTE

Pressure Washer Range



The Nilfisk DTE range of pressure washers are made in the UK and are designed to cope with continuous use in the most demanding operator environments.

Focused on efficiency we specialise in supplying robust industrial pressure washers. The Nilfisk DTE range includes both mobile and stationary hot and cold water pressure washers.

The Nilfisk DTE machines are easy to operate and maintain. They are built with a robust stainless steel cover & stone enamelled steel chassis for durability and excellent reliability resulting in reduced service time & costs.

Each of the machines can also come in multiple different variants of; pressure, flows, sizes and accessories that will best suit your specific needs.

Ideally suited for:

- Automotive Industry
- Valeters
- Vehicle Hire Companies
- Manufacturing & Warehousing
- Plant Hire
- Rail Industry
- Franchised Dealers
- Independent Garages
- Logistics / Distribution



Cold Water Pressure Washers



400CS
Static



400CM
Mobile

- Low revving brass pump for increased working life and durability
- Ceramic sleeved pistons for durability and extended working life
- Robust stainless steel cover and stove enamelled steel chassis for durability and excellent reliability resulting in reduced service time and costs.
- All models include industrial gun, lance and 9 metre twin wire hose as standard accessories

Hot Water Pressure Washers



400HM
Mobile



400HS
Static

- Robust design for excellent reliability and a reduction in service time and costs
- Low revving pump for increased working life and durability
- High Pressure Chemical System improves cleaning performance with the efficient use of chemicals
- All models include industrial gun, lance and 9 metre twin wire hose as standard accessories

COLD WATER TECHNICAL DATA

| | 400CS 240V | 400CS 415V | 400CS 415V | 400CM 110V | 400CM 240V | 400CM 415V |
|----------------------------------|--|------------|-------------|--------------------|------------|--------------------|
| Max working pressure (bar/psi) | 100/1450 | 150/2175 | 200/3000 | 100/1450 | 100/1450 | 150/2175 |
| Max water flow rate (litres/min) | 12 | 15 | 15 | 12 | 12 | 15 |
| Max water inlet temp (°C) | 60 | 60 | 60 | 60 | 60 | 60 |
| Motor (HP/kW/v) | 3/2.2/240 | 5.5/4/415 | 7.5/5.5/415 | 3/2.2/110 | 3/2.2/240 | 7.5/5.5/415 |
| Pump type | Brass with 3 ceramic pistons, stainless steel valves and fibre seals | | | | | |
| Chassis/Cover | Stone enamelled / stainless steel | | | | | |
| Dimensions (mm) | L500 x W750 x H400 | | | L900 x W500 x H875 | | L930 x W580 x H820 |
| Weight (kg) | 60 | 60 | 60 | 50 | 50 | 60 |
| ITEM NO. | UK15A0110 | UK15A0114 | UK15A0111 | UK15A0102 | UK15A0100 | UK15A0103 |

HOT WATER TECHNICAL DATA

| | 400HS 240V | 400HS 415V | 400HS 415V | 400HM 110V | 400HM 240V | 400HM 415V | 500HM 415V |
|----------------------------------|--|------------|-------------|-----------------------------------|------------|------------|-------------|
| Max working pressure (bar/psi) | 100/1450 | 150/2175 | 200/3000 | 100/1450 | 100/1450 | 150/2200 | 200/3000 |
| Max water flow rate (litres/min) | 12 | 15 | 15 | 12 | 12 | 15 | 15 |
| Max water inlet temp (°C) | 50 | 50 | 50 | 80 | 80 | 80 | 80 |
| Motor (HP/kW/v) | 3/2.2/240 | 5.5/4/415 | 7.5/5.5/415 | 3/2.2/110 | 3/2.2/240 | 5.5/4/415 | 7.5/5.5/415 |
| Pump type | Brass with 3 ceramic pistons, stainless steel valves and fibre seals | | | | | | |
| Chassis/Cover | Stove enamelled / stainless steel (full stainless steel available) | | | Stove enamelled / stainless steel | | | |
| Dimensions (mm) | L600 x W850 x H1750 | | | L1150 x W735 x H720 | | | |
| Weight (kg) | 250 | 250 | 250 | 160 | 160 | 160 | 160 |
| ITEM NO. | UK15A0307 | UK15A0311 | UK15A0309 | UK15A0301 | UK15A0317 | UK15A0302 | UK15A0306 |

Nilfisk Ltd

Nilfisk House · Bowerbank Way · Gilwilly Industrial Estate · Penrith · Cumbria · CA11 9BQ
 Tel.: 01768 868995 (UK) · 01 2943838 (IE)
 Email: sales.uk@nilfisk.com (UK & IE)
 www.nilfisk.co.uk · www.nilfisk.ie

