

Ausführungen | Versions ST-6

Bezeichnung Description	E Eingang Inlet	A Ausgang Outlet	M Manometer Gauge	L PVC-Leitung PVC-cable	Schwimmer Float	Artikel-Nr. Item-No.
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1200 mm	12,3 mm	20 0006 500
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1850 mm	12,3 mm	20 0006 501
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1200 mm	12,1 mm	20 0006 510
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	1200 mm	12,5 mm	20 0006 530
Strömungswächter Flowswitch	G3/8 AG G3/8 male	G3/8 AG G3/8 male	G1/4 IG G1/4 female	ohne Schalter without switch	12,5 mm	20 0006 535
Strömungswächter Flowswitch	3/8"NPT AG 3/8"NPT male	3/8"NPT AG 3/8"NPT male	G1/4 IG G1/4 female	1200 mm	12,3 mm	20 0006 540

Technische Daten | Specification

Druck Pressure	310 bar 4500 psi
Durchfluss Flow rate	30 l/min 8 US gal/min
Kontaktart Contact	Schließer Normally open
Spannung Voltage	250 V AC / DC
Strom Current	3 A
Leistung rupturing capacity	120 VA
Schaltzeit Response time	35 ms
Temperatur Temperature	80 °C 176 °F
Gewicht Weight	0,37 kg

