




PA S.p.A. - High pressure washing accessories

Via Milano, 13 - 42048 RUBIERA (REGGIO EMILIA) - ITALY - Tel. +39 0522 623611 - Fax +39 0522 629600

<http://www.pa-etl.it> - E-mail: info@pa-etl.it

CORPORATE NAME					
CHARACTERISTICS OF THE SYSTEM					
PUMP FLOW RATE	L/min				
PRESSURE AT INLET OF THE TANK CLEANING HEAD	bar				
WASHING MODE					
HOT WATER WASHING (specify temperature)	°C				
COLD WATER WASHING	°C				
REQUESTED WASHING CYCLE:	min.				
PRODUCT TO BE REMOVED					
WASHING LIQUID					
IMPORTANT, SPECIFY THE DETERGENT, ITS CHEMICAL COMPOSITION AND MIXING PERCENTAGE IF ANY:					
1)					
2)					
3)					
4)					
The standard cleaning head is supplied with EPDM dynamic seals. On request they can be supplied in the following materials: NBR (nitrile), FKM (viton), FFKM (kalrez).					
INDICATIVE DIMENSIONS OF THE CONTAINER TO BE WASHED					
CONTAINER SHAPE "A" 		d (cm)=		how many =	
		G (cm)=			
		D (cm)=			
		L (cm)=			
		SEPARATORS (S)			
		YES		NO	
		how many =			
CONTAINER SHAPE "B1" 	CONTAINER SHAPE "B2" 	CONTAINER SHAPE "B1"			
		d (cm)=			
		D (cm)=			
		L (cm)=			
		CONTAINER SHAPE "B2"			
		d (cm)=			
		E (cm)=			
F (cm)=					
H (cm)=					
ATEX MARKING REQUIRED (FOR USE IN EXPLOSIVE SURROUDINGS)				YES	NO
ATEX VERSION AVAILABLE - CATEGORY 1 - ZONE 0 ⇒ 20					
IN THE A80R VERSION, THE HEAD HANGS INSIDE THE TANK FROM A:		PIPE		HOSE	
ORDER INFORMATION					
CLEANING HEAD:		Serial N°			
INFO ON THE TANK CLEANING HEAD:		P/N:	- Q.ty:		
INFO ON THE NOZZLES:		P/N:	- Q.ty:		
NOZZLE PROTECTION (P/N: 25.4822.00)		YES		NO	

Date of compilation

TABELLA SCELTA UGELLO TESTINA - NOZZLE SELECTION CHART FOR CLEANING HEADS

Fatt.Portata							
SIZE	↓	M4 (CORTI) (0°)	M4 (0°)	1/4 NPT (5°) Standard	Con ventolina 1/8 NPT (0°) Standard	With flow straightener	
						1/4 NPT (0°) Standard	1/4 NPT (0°) Prol-Extended
O2	4,6 1,2	80.0350.51	25.1190.51		16.1363.20		
O23	5,0 1,3		25.1191.51				
O25	5,6 1,5	80.0351.51	25.1091.51				
O27	6,1 1,6		25.1192.51				
O3	6,7 1,8	80.0352.51	25.1092.51	16.1305.30	16.1363.30	16.1380.30	
O32	7,1 1,9		25.1193.51				
O35	7,8 2,1	80.0353.51	25.1093.51			16.1380.35	
O37	8,4 2,2		25.1098.51				
O4	9,1 2,4	80.0354.51	25.1094.51	16.1305.40	16.1363.40	16.1380.40	
O43	9,7 2,6		25.1194.51				
O45	10,3 2,7		25.1095.51		16.1363.45	16.1380.45	
O5	11,2 3,0		25.1195.51	16.1305.50	16.1363.50	16.1380.50	
O53	12,0 3,2		25.1196.51				
O55	12,6 3,3		25.1197.51			16.1380.55	
O6	13,7 3,6		25.1186.51	16.1305.60	16.1363.60	16.1380.60	
O65	14,8 3,9		25.1198.51			16.1380.65	
O7	16,0 4,2		25.1199.51	16.1305.70	16.1363.70	16.1380.70	80.0418.23
O8	18,2 4,8		25.1085.51	16.1305.80	16.1363.80		80.0419.23
O9	21,0 5,5				16.1363.90		80.0420.23
O95	22,0 5,8						80.0421.23
11	25,0 6,6						80.0422.23
12	27,0 7,1						80.0423.23
13	30,0 7,9						80.0424.23
14	32,0 8,5						80.0425.23
15	34,0 9,0				16.1363.15		80.0426.23
16	36,0 9,5						80.0427.23
18	41,0 10,8						80.0428.23
19	43,0 11,4						80.0429.23
20	46,0 12,2						80.0430.23
25	57,0 15,1						80.0435.23
30	68,0 18,0						80.0440.23